

Table 10.2. 2021 Drill intersection highlights showing results above 0.1 g/t Au.

Hole	Depth	Incline	Bearing	Interval-Ft	Thickness-Ft*	Au g/t	Au opt	High Assay Au g/t	Low Assay Au g/t	Number of samples in interval	Number of samples <0.1 Au g/t	Comments
WR-15	500	-90	0 <i>Including</i>	120-215	95	0.636	0.0185	2.348	0.094	19	1	Twin WR-3
				160-185	25	1.452	0.042	2.348	0.974	5		
				235-410	175	0.197	0.0058	1.088	0.075	35	4	
				240-265	25	0.427	0.012	1.088	0.15	5		
				420-435	15	0.13	0.004	0.151	0.109	3		
WR-16**	300	-50	90 <i>Including</i> <i>Including</i>	95-270	180	0.618	0.018	3.545	0.09	36	1	
				95-135	40	0.83	0.024	3.545	0.103	8		
				225-260	35	1.53	0.044	2.74	0.414	7		
WR-17**	450	-50	270	440-450	10	0.21	0.006	0.314	0.107	2		
WR-18**	320	-50	180	295-320	25	1	0.029	3.206	0.189	5		
WR-19**	300	-50	0	90-125	35	0.792	0.023	3.227	0.143	7		Rods stuck
				150-175	25	0.321	0.009	0.741	0.161	5		
				290-300	10	0.404	0.012	0.454	0.355	2		
WR-20	450	-50	90	85-115	25	0.158	0.005	0.244	0.057	5	1	
				165-230	65	0.196	0.006	0.333	0.075	13	2	
				255-280	25	0.321	0.009	0.352	0.088	5	1	
WR-21	400	-50	270	110-135	25	0.11	0.003	0.137	0.092	5	1	
WR-22**	140	-90	0	0-40	40	0.357	0.01	0.712	0.122	8		Twin RR-3
				60-65	5	1.337	0.039	1.337	1.337	1		
				85-140	55	0.25	0.007	0.423	0.155	11		
WR-23	480	-45	260 <i>Including</i> <i>Including</i>	0-75	75	0.256	0.007	0.417	0.111	15		Twin RR-38
				95-360	265	0.388	0.011	1.51	0.112	53		
				100-125	25	0.778	0.023	1.086	0.371	5		
				160-180	20	0.397	0.012	0.631	0.231	4		

Hole	Depth	Incline	Bearing	Interval-Ft	Thickness-Ft*	Au g/t	Au opt	High Assay Au g/t	Low Assay Au g/t	Number of samples in interval	Number of samples <0.1 Au g/t	Comments
			<i>Including</i>	200-220	20	0.526	0.015	0.653	0.453	4		
			<i>Including</i>	260-310	50	0.65	0.019	1.51	0.143	10		
WR-24**	300	-60	260	0-40	40	0.454	0.013	0.9	0.178	8		
				90-300	210	0.293	0.009	1.288	0.04	42	1	
			<i>Including</i>	95-130	35	0.713	0.021	1.288	0.376	7		
			<i>Including</i>	230-240	10	0.407	0.012	0.413	0.401	2		
WR-25**	200	-50	60	55-95	40	0.301	0.009	0.478	0.122	8		
				105-125	20	0.14	0.004	0.213	0.107	4		
				140-165	25	0.144	0.004	0.245	0.098	5	1	
WR-26	400	-90	0	0-55	55	0.157	0.005	0.437	0.09	11	1	
				80-150	70	0.293	0.009	0.807	0.141	14		
				175-190	15	0.117	0.003	0.125	0.105	3		
				200-330	130	0.241	0.007	0.62	0.105	26		
			<i>Including</i>	235-255	25	0.435	0.013	0.62	0.282	5		
				345-380	35	0.156	0.005	0.191	0.126	7		
WR-27**	300	-50	120	10-15	10	0.82	0.024	1.413	0.228	2		
				30-55	25	0.237	0.007	0.389	0.114	5		
				70-210	140	0.257	0.007	0.94	0.076	28	3	
			<i>Including</i>	115-140	25	0.546	0.016	0.94	0.325	5		
WR-28	530	-90	0	75-340	265	0.376	0.011	1.278	0.101	53		Rods stuck
			<i>Including</i>	205-260	55	0.729	0.021	1.278	0.366	11		
				355-405	50	0.242	0.007	0.488	0.113	10		
WR-29**	235	-50	90	115-235	120	0.276	0.008	0.578	0.08	24	1	
WR-30**	140	-50	270	85-140	55	0.291	0.009	0.518	0.126	11		
WR-31	400	-80	90	195-335	140	0.208	0.006	0.819	0.084	28		

Hole	Depth	Incline	Bearing	Interval-Ft	Thickness-Ft*	Au g/t	Au opt	High Assay Au g/t	Low Assay Au g/t	Number of samples in interval	Number of samples <0.1 Au g/t	Comments
WR-32**	380	-60	120	165-380	215	0.305	0.009	0.638	0.116	43		Twin WR-7
				<i>Including</i> 175-240	65	0.411	0.012	0.638	0.201	13		
				<i>Including</i> 350-365	15	0.492	0.014	0.53	0.455	3		
WR-33**	120	-90	0	75-120	45	0.39	0.011	0.799	0.197	9		
WR-34**	150	-50	90	0-20	20	0.17	0.005	0.228	0.108	4		
				95-140	45	0.492	0.014	1.292	0.125	9		
				<i>Including</i> 95-120	25	0.96	0.028	1.292	0.508	5		
WR-35**	160	-50	0	110-160	50	0.22	0.006	0.373	0.083	10	1	
WR-36**	250	-50	270	115-250	135	0.242	0.007	0.611	0.106	27		
				<i>Including</i> 215-235	20	0.412	0.012	0.611	0.285	4		
WR-37	600	-50	180	35-50	15	0.23	0.007	0.288	0.182	3		
				70-100	30	0.153	0.004	0.233	0.11	6		
				210-225	15	0.157	0.005	0.236	0.112	3		
				240-285	45	0.226	0.007	0.442	0.1	9		
				310-405	95	0.205	0.006	0.536	0.083	19	1	
				490-500	10	0.119	0.003	0.137	0.101	2		
				590-600	10	0.182	0.005	0.233	0.131	2		
WR-38**	270	-90	0	120-175	55	0.28	0.008	1.064	0.092	11	3	Rods stuck
				<i>Including</i> 135-160	25	0.476	0.014	1.064	0.281	5		
				200-225	25	0.156	0.005	0.216	0.106	5		
				245-265	20	0.216	0.006	0.297	0.177	4		
WR-39**	220	-70	270	65-90	25	0.152	0.004	0.269	0.102	5		
				125-150	25	0.217	0.006	0.35	0.086	5	1	
				195-220	25	0.17	0.005	0.308	0.081	5	1	
WR-40**	220	-50	270	135-220	85	0.449	0.013	1.278	0.104	17		
WR-41**	250	-50	225	145-195	50	0.289	0.008	1.068	0.071	10	1	

Hole	Depth	Incline	Bearing	Interval-Ft	Thickness-Ft*	Au g/t	Au opt	High Assay Au g/t	Low Assay Au g/t	Number of samples in interval	Number of samples <0.1 Au g/t	Comments
				215-250	35	0.219	0.006	0.311	0.111	7		
WR-42	360	-50	90	0-30	30	0.16	0.005	0.269	0.105	6		
				185-250	65	0.15	0.004	0.245	0.084	13	1	
				260-280	20	0.24	0.007	0.318	0.187	4		
WR-43**	200	-45	270	40-200	160	0.017	0.005	0.258	0.063	32	3	
WR-44	320	-45	90	95-145	50	0.137	0.004	0.217	0.08	10	1	
WR-45	340	-80	180	55-275	220	0.517	0.015	1.848	0.095	44		
			<i>Including</i>	70-170	100	0.88	0.026	1.848	0.441	20		
			<i>Including</i>	120-160	40	1.11	0.032	1.848	0.705	8		
WR-46**	60	-50	270	0-60	60	0.367	0.011	1.778	0.075	12	1	
			<i>Including</i>	35-50	15	1.01	0.029	1.778	0.591	3		
WR-47	310	-65	270	0-310	310	0.359	0.01	1.778	0.08	62	1	
			<i>Including</i>	35-135	100	0.535	0.016	1.778	0.185	20		
			<i>Including</i>	170-195	25	0.717	0.021	1.163	0.318	5		
WR-48	300	-45	270	160-180	20	0.1	0.003	0.116	0.092	4	3	
				220-225	10	0.1	0.003	0.142	0.126	2		
WR-49	300	-50	90	60-85	25	0.1	0.003	0.123	0.071	5	1	

*True widths are not known at present

**Hole ended prematurely due to drilling conditions